

Leclanché Capacitors  
48, av. de Grandson  
1400 Yverdon, Switzerland



Tel. +41 24 445 66 88  
Fax +41 24 445 66 89  
[capinfo@Lcap.ch](mailto:capinfo@Lcap.ch)  
[www.Lcap.ch](http://www.Lcap.ch)

Drawing No. : 1027463  
created from : 08/07/2014 17:28:00

**Part Number : GA68210075143**

	$\varnothing D$ : 75 mm L : 143 mm a : 31,7 mm h : 5 mm :	Insulated at the base.
	Terminals : M5	

**Electrical Parameter**

Rated Capacitance ( $C_R$ ) @ 100 Hz / 20 °C	<b>6800</b> $\mu$ F	
Tolerance	<b>-10, +30</b> %	
Rated Voltage ( $U_R$ )	<b>100</b> V	
Surge Voltage ( $U_S$ ) max. 5 x 1 min / h	<b>115</b> V	
Reverse Voltage ( $U_U$ ) max. 1 s	<b>2</b> V	
Leakage Current ( $I_L$ ) @ $U_R$ / 5 min / 20 °C	<b>1400</b> $\mu$ A	
ESR typ. @ 100 Hz / 20°C	<b>23</b> m $\Omega$	
Tan $\delta$ typ. @ 100 Hz / 20°C	<b>10</b> %	
Z max. @ 10 kHz / 20°C	<b>19</b> m $\Omega$	
ESL typ.	<b>20</b> nH	
Rated Ripple Current ( $I_R$ ) @ 100 Hz / 105 °C	<b>9,5</b> A	
Useful life @ $I_R, U_R, 105$ °C	<b>8000</b> h	2000 h@20 A ( $\Delta T_{over} = 20^\circ C$ ) 1000 h@24A ( $\Delta T_{over} = 30^\circ C$ )
IEC Climatic category / Standards	<b>55/105/56</b>	<b>IEC 60384-4</b>
Applications	General Industrial	
Your article No. / Project		