

Leclanché Capacitors
48, av. de Grandson
1400 Yverdon, Switzerland



Tel. +41 24 445 66 88
Fax +41 24 445 66 89
capinfo@Lcap.ch
www.Lcap.ch

Drawing No. : 1027471-53567
created from : 12/08/2014 08:18:00

Part Number : GBE11250040100

	$\varnothing D$: 40 mm L : 100 mm a : 18 mm h : 5 mm B : M12 Terminals : M5

Electrical Parameter

Rated Capacitance (C_R) @ 100 Hz / 20 °C	1150 μ F	
Tolerance	-10 +30 %	
Rated Voltage (U_R)	500 V	
Surge Voltage (U_S) max. 5 x 1 min / h	525 V	
Reverse Voltage (U_U) max. 1 s	2 V	
Leakage Current (I_L) @ U_R / 5 min / 20 °C	3450 μ A	
ESR typ. @ 100 Hz / 20°C	111 m Ω	
Tan δ typ. @ 100 Hz / 20°C	8 %	
Z max. @ 10 kHz / 20°C	89 m Ω	
ESL typ.	20 nH	
Useful life , No. of Flash @ $I_R, U_R, 60$ °C	7 200 000 Flash	
IEC Climatic category / Standards	40/060/56	IEC 60384-4
Applications	Flash Application	
Your article No. / Project		