

Leclanché Capacitors
48, av. de Grandson
1400 Yverdon, Switzerland



Tel. +41 24 445 66 88
Fax +41 24 445 66 89
capinfo@Lcap.ch
www.Lcap.ch

Drawing No. : 1027642-53567
created from : hs 28/08/2014 07:13:00

Part Number : SI4PHE22136035040

	<p> $\varnothing D$: 35 mm L : 40 mm h : 6,3 mm </p> <p> Insulation : PVC 2500 Vac Terminals : Snap In </p>	<p>Drill plan</p> <p>NC terminals are not to be connected to the electrical circuit!</p>
--	--	--

Electrical Parameter

Rated Capacitance (C_R) @ 100 Hz / 20 °C	220 μ F	
Tolerance	±10 %	
Rated Voltage (U_R)	360 V	
Surge Voltage (U_S) max. 5 x 1 min / h	380 V	
Reverse Voltage (U_U) max. 1 s	2 V	
Leakage Current (I_L) @ U_R / 5 min / 20 °C	237 μ A	
ESR typ. @ 100 Hz / 20°C	170 m Ω	
Tan δ typ. @ 100 Hz / 20°C	3 %	
Z max. @ 10 kHz / 20°C	326 m Ω	
ESL typ.	20 nH	
Max Peak Current	350 A	
Useful life, No. of Flash @ $I_R, U_R, 105$ °C	10 000 000 Flash	@ 2 s (0,5 Hz)
IEC Climatic category / Standards	40/105/56	IEC 60384-4
Applications	Flash application	
Your article No. / Project		