

Leclanché Capacitors
48, av. de Grandson
1400 Yverdon, Switzerland



Tel. +41 24 445 66 88
Fax +41 24 445 66 89
capinfo@Lcap.ch
www.Lcap.ch

Drawing No. : 1027474
created from : 15/07/2014 13:20:00

Part Number : SIH33303535045

	$\varnothing D$: 35 mm L : 45 mm h : 6,3 mm
	Insulation : PVC 2500 Vac Terminals : Snap In

Electrical Parameter

Rated Capacitance (C_R) @ 100 Hz / 20 °C	33000 μ F	
Tolerance	±20 %	
Rated Voltage (U_R)	35 V	
Surge Voltage (U_S) max. 5 x 1 min / h	40 V	
Reverse Voltage (U_U) max. 1 s	2 V	
Leakage Current (I_L) @ U_R / 5 min / 20 °C	6930 μ A	
ESR typ. @ 100 Hz / 20°C	5 m Ω	
Tan δ typ. @ 100 Hz / 20°C	10 %	
Z max. @ 10 kHz / 20°C	2 m Ω	
ESL typ.	20 nH	
Rated Ripple Current (I_R) @ 100 Hz / 105 °C	8,3 A	
Useful life @ I_R , U_R , 105 °C	5000 h	
IEC Climatic category / Standards	55/105/56	IEC 60384-4
Applications	General Industrial	
Your article No. / Project		