


#5902

HIGH TEMPERATURE FILM CAPACITORS

MKS 4-1.5 v F



Dielectric of metallized polyphenylene sulfide - Metal case, non magnetic

Glas sealed - Plastic sleeve transparent

Parameter	Symbol		Value	Unit	Condition
Capacitance	C		1.5	$\mu\text{F}$	1 V / 1 kHz
Tolerance			$\pm 1$	%	
Rated voltage	Un DC		40	VDC	
Tangent delta	tg $\delta$		$\leq 20$	$10^{-4}$	1 V / 1 kHz / 22°C
Stray inductance	ESL		$\leq 50$	nH	
Insulation resistance	Ri		$> 3330$	M $\Omega$	40 VDC - 1 min
Test voltage between terminals	U T1		63	VDC	10 s
Operating temperature			- 55 to + 125	°C	
Dimension	Symbol			Unit	Conditions
Diameter	D		$12.7 \pm 1.0$	mm	
Length	L		$22.0 \pm 1.0$	mm	
Terminals					
Axial tinned wire	d		0.8	mm	
	M1				
	M0				
	Modification	Date	Visa émetteur		

Condensateurs CH 1400 Yverdon-les-Bains  
 Kondensatoren Tel.: ++41 24 445 66 88  
 Capacitors Fax: ++41 24 445 66 89

**Le Lanché**  
**Capacitors**  
A FISCHER & TAUSSCHER COMPANY

HJJ

15.02.2010

faisab5902.XLS